1

Low Rate Pellet or Powder Feeders

Disc Feeders 50, 100, 150, 200 Basic Volumetric Feeder with standard controller

- Includes PLC contoroller with color touchscreen
- Set-up for batch control for IMM and extrusion follower for extrusion
- Stepper motor technology for the 50, 100 & 150 units
- AC or DC technology for the 100, 150, 200
- Quick material change overs with spare feeders
- Unlimited disc designs (thin, thick) (hole designs)
- Can accommodate mutiple feeders Syncroblend
- Dithering design
- Dual outlet design
- Feeding capability 1g/hr 800lbs/hr

Optional

- Batch Blender integration
- Continuous L-I-W configuration

Series 50

Typical rates .002-0.22 mg-g/hr Materials powder, granulate, micro pellet Set-up for Batching, and Continuous feeding Alarms Multi-component capable Touch screen with PLC

Series 100

Typical rates 0.002-200 lbs/hr Materials powder, granulate, pellet, flake Set-up for Batching, and Continuous feeding Alarms Multi-component capable

Series 150

Typical rates .5-300 lb/hr Materials powder, granulate, pellet, flake Set-up for Batching, and Continuous feeding Alarms Multi-component capable

Series 200

Standard designed Disc 72-10 Hole Typical rates 0.5 - 800 lbs/hr Materials powder, granulate, pellet, flake Set-up for Batching and Continuous feeding Alarms



